Solis

THE TOUGHEST PERFORMER FOR YOUR FIELD

S 26

- RELIABLE MECHANICAL TRACTOR
- POWER PACKED ENGINE
- TWIN PROJECTOR HEADLAMPS
- AGRI, IND. & TURF TYRE OPTION
- REINFORCED SAFETY FEATURES

CELEBRATING 1,700,000 TRACTORS GLOBALLY

COST EFFICIENT MECHANICAL TRACTORS

MADE OF REAL STEEL

STRATEGIC COLLABORATION WITH YANMAR

THE TOUGHEST PERFORMER FOR YOUR FIELD

S 26

Solis

FEATURES	S 26
ENGINE	
Engine Type	MHI Engine
HP Category	26
No. of Cylinders	3
Aspiration	Natural
Cubic Capacity (cc)	1318
Rated RPM	2700
Air Cleaner	Dry Type with Clogging Sensor
Cold Start	Standard
Max Torque (Nm)	76.3 Nm
Exhaust	Downdraft Exhaust
Muffler	Under-hood
TRANSMISSION	
Drive	4WD
Clutch	Single Clutch
Gearbox	6F+2R
Front Axle	4WD
Transmission	Sliding Mesh
SPEED (FORWARD) Agri Tyre	
Maximum Speed (Km/Hr)	18.08
Minimum Speed (Km/Hr)	1.67 @ 2700 erpm Speeds May Vary with Other Tyres
BRAKES	
Brakes	Oil Immersed Brakes
Type of Actuation	Mechanical
Parking Brake	Independent
DIFFERENTIAL LOCK	
Differential Lock	Mechanical, Foot Operated
PTO	
PTO (RPM)	540/1000
PTO (Actuation)	Mechanical
STEERING	
Steering	Power
ELECTRICAL	
Battery	12V, 65Ah
Alternator	12V, 42Amp
Seven Pin Trailer Socket	Output 12V
HYDRAULICS	
3 Point Linkage	Cat 1-N
Stay Bars	Anchor Chain
Hydraulic Lifting Capacity (Kg)	600
Auxiliary Hydraulic Circuit	1DA
SAFETY SWITCH	
Clutch Safety Switch	Standard

FEATURES	S 26
PTO Safety Switch	Standard
Neutral Safety Switch	Standard
CAPACITY (Ltrs.) (+/-5%)	
Fuel Tank (Ltr.)	26
TURNING RADIUS	
With Brakes (m)	2.7
TYRE	
Front	6.00 - 12
Rear	8.30 - 20
DIMENSION & WEIGHT (+/-5%) Agri Tyre	
Weight (Kg)	995
Wheel Base (mm)	1560
Total Length (mm)	2760
Total Width (mm)	1075
Height (mm) Up to ROPS	1955
Min. Ground Clearance (mm)	240
Front Track (mm)	885
Rear Track (mm)	835
OTHERS	
Fuel Indicator Gauge	Standard
Front Tow Hook	Standard
Front & Rear Weights with Std. Ballast	Front Weights - 15 x 2
Trailer Hitch	1. Swinging Bar (Optional)
	2. Clevis Hitch (Standard)
	3. Semi Automatic Hitch
Roll Over Protection	Standard
Canopy	Optional
OPTIONAL FEATURES	
TYRES	

TURF Front Tyre: 23x8.50-12 Rear Tyre: 33x15.50-16.5	**INDUSTRIAL** Front Tyre: 23x8.50-12 Rear Tyre: 33x15.50-16.5	**AGRI** Front Tyre: 7x14 Rear Tyre: 8.3x24	**RADIAL** Front Tyre: 6.5/80-12 Rear Tyre: 280/70 R18	**GALAXY PRO** Front Tyre: 220/55 R12 Rear Tyre: 280/70 R16

Front End Loader	Optional

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

DEALER STAMP

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221
Fax:+91- 01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com