

# Solis

— THE TOUGHEST —  
**PERFORMER**  
« FOR YOUR FIELD »

**26**  
SHUTTLE XL



INTEGRATED  
LOADER  
JOYSTICK (OPTIONAL)

MULTI TIRE OPTIONS  
(AGRI, INDUSTRIAL  
& TURF TYRE)

QUICK ATTACHED  
LOADER

SYNCHROMESH  
SHUTTLE

9 FORWARD  
X 9 REVERSED GEAR



**COST  
EFFICIENT**  
MECHANICAL TRACTORS

MADE OF  
**REAL  
STEEL**

STRATEGIC  
COLLABORATION  
WITH  
**YANMAR**

**THE TOUGHEST  
PERFORMER  
« FOR YOUR FIELD »**

**26  
SHUTTLEXL**

**Solis**



FEATURES		26 SHUTTLEXL (9+9)
<b>ENGINE</b>		
Engine Type	Mitsubishi 3-Cylinder Diesel Engine	
HP Category	26	
No. of Cylinders	3	
Aspiration	Naturally	
Cubic Capacity (cc)	1319	
Rated RPM (+/-25mm)	2500	
Air Cleaner	Dry	
Cold Start	Standard	
Max Torque (Nm)	76.3	
Exhaust	Silencer in the Engine Compartment, Downward Discharge	
<b>TRANSMISSION</b>		
Drive	4 WD	
Clutch	Single Clutch	
Gearbox	9 Forward + 9 Reverse	
Front Axle	4WD	
Transmission	Constant Mesh with Synchromesh Shuttle Lever	
<b>SPEED (FORWARD) AGRI TYRE</b>		
Maximum Speed (Km/Hr)	19.71	
Minimum Speed (Km/Hr)	1.14	
<b>BRAKES</b>		
Brakes	Oil Immersed	
Type of Actuation	Mechanical	
Parking Brake	Independent	
<b>DIFFERENTIAL LOCK</b>		
Differential Lock	Yes, Foot Operated	
<b>PTO</b>		
PTO (rpm)	540/540E	
PTO (Actuation)	Mechanical	
<b>STEERING</b>		
Steering	Power steering	
<b>ELECTRICAL</b>		
Battery	12V, 65 Ah	
Alternator	12V, 42 A	
Seven Pin Trailer Socket	Standard	
<b>HYDRAULICS</b>		
3 Point Linkage	Cat 1-N	
Stay Bars	Anchor Chain	
Additional Hydraulic Circuit	1DA	
Hydraulic Lifting Capacity (Kg)	600	
Lift Rods	Standard	
Litre per Minute (LPM)	17.8	
<b>SAFETY SWITCH</b>		
PTO Safety	Standard	

FEATURES		26 SHUTTLEXL (9+9)	
Neutral Safety Switch	Standard		
Clutch Safety Switch	Standard		
<b>CAPACITY (LTRS)(+/-5%)</b>			
Fuel Tank (Ltr.)	20		
<b>TURNING RADIUS</b>			
Without Brakes (m) as per Standard Tyres	3.06		
<b>TYRE</b>			
Front	6.00-12		
Rear	8.30-20		
<b>DIMENSION &amp; WEIGHT(+/-5%) AGRI TYRE</b>			
Weight (Kg)	1045		
Wheel Base (mm)	1570		
Total Length (mm)	2895		
Total Width (mm)	1215 (min) - 1290 (max)		
Height (mm) Up to ROPS	2440		
Min Ground Clearance (mm)	240		
Front Track (mm)	880-990		
Rear Track (mm)	920-1000		
<b>OTHERS</b>			
Fuel Indicator Gauge	Standard		
Front Tow Hook	Standard		
Front & Rear Weights with Std. Ballast	Front Weights-2 x 15		
Trailer Hitch	1. Clevis Hitch (Optional) 2. Semi Automatic Hitch 3. E-Marked Swinging Drawbar		
ROPS	Standard		
<b>OPTIONAL FEATURES</b>			
Cabin Option	Optional Only Heater		
<b>TYRES</b>			
<b>RADIAL AGRI</b>	<b>TURF</b>	<b>INDUSTRIAL</b>	<b>GALAXY PRO</b>
Front Tyre: 6.5/80-12 Rear Tyre: 280/70 R18	Front Tyre: 25x8.50-14 Rear Tyre: 13.60-16	Front Tyre: 23x8.50-12 Rear Tyre: 33x15.5-16.5	Front Tyre: 220/55 R12 Rear Tyre: 280/70 R16
Front loader	Yes Optional		

**DEALER STAMP**



\*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

**INTERNATIONAL TRACTORS LIMITED**

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)  
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221  
Fax:+91- 01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com